

# ANPx341/RES/UHV - linear x-nanopositioner

1006755

## Technical Specifications

<b>Size and Dimensions</b>	
footprint; height	44 mm x 45 mm; 11.5 mm
maximum installation space	44 mm x 61 mm x 11.5 mm
weight	82.2 g
height	11.5 mm
cable	30 cm cable with connector
<b>Materials</b>	
positioner body	titanium
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
<b>Coarse Positioning Mode</b>	
travel range (step mode)	20 mm
maximum drive velocity @ 300 K	~ 3 mm/s
input voltage range	0 - 60 V
<b>Fine Positioning Mode</b>	
fine linear positioning range @ 300 K	5 $\mu$ m
fine positioning resolution	sub-nm
input DC voltage range @ 300 K	0 - 100 V
<b>Position Encoder</b>	
readout mechanism	resistive sensor
encoded travel range	full travel
sensor resolution	~ 200 nm
sensor power (when measuring)	0.01 - 1 mW
repeatability	1..2 $\mu$ m (unidirectional)
<b>Load (@ ambient conditions)</b>	
maximum load	2 kg
maximum dynamic force along the axis	2 N
<b>General Specifications</b>	
environment	/UHV

