

ECGt5050/AI/HL/NUM/RT

1008844

Technical Specifications

Size and Dimensions	
footprint; height	50 mm x 50 mm; 17 mm
distance center of rotation to bottom	77 mm
maximum installation space	50 mm x 67.6 mm; 19.4 mm
weight (aluminium version)	137 g
height	17 mm
cable	50 cm cable with connector
Materials	
positioner body	aluminum
actuator	PZT ceramics
connecting wires	copper, jacket: RT: PTFE, HV/UHV: fiberglass
Coarse Positioning Mode	
travel range (step mode)	10 °
maximum drive velocity @ 300 K	3 °/s
input voltage range	0 - 45 V
Fine Positioning Mode	
fine angular positioning range @ 300 K	1.4 m °
fine positioning resolution	μ °
input DC voltage range	0 - 45 V
Position Encoder	
readout mechanism	optoelectronic sensor
encoded travel range	entire travel
sensor resolution	1 μ °
sensor power (when measuring)	300 mW
repeatability	50 μ ° (bidirectional)
Load (@ ambient conditions)	
maximum load	1 kg
maximum dynamic torque around axis	35 Ncm
General Specifications	
environment	/RT
operating temperature range	17 - 25 °C
operating humidity range	40 - 60%

